



- BOUNDARY TREATMENT**
- Feature Brick Wall
Min. 1.8 m high, 250 thick exposed brick wall and/or flint wall, 600 (L) x 280 (w), 50 thick concrete coping, concrete footing to Engineer's specifications
 - Fence Type 1 - Fence Between Houses
Close board fence, 1.8m high, taper sawn, Timber support posts 125 x 100mm, 2.7 m long, with min 3 arris rails, 2.4 m c/c fixed in ground to Manufacturer's specification. Matching entrance gates to be installed where applicable
 - Fence Type 2 - Fence around Play Area
1.1 m high, bow top railing (as per RoSPA guidelines), powder coated black, fixing as per manufactures details. Supplier: HERAS or similar approved, Product: Tangorail TR800 play
 - Railing Type 1 - Metal Railing to Vehicular Bridge.
Bespoke metal fence, 1.1 m high, Grade 316 Stainless Steel, Finish: Powder coated, Colour: Matt Black RAL9005
 - Railing Type 2 - Timber Railing to Deck and Boardwalk,
Bespoke timber fence 1.10 m high. Posts at 2.4m c/c fixed in concrete.
 - Railing Type 3 - Knee Rails
0.3 m high, 100 x 100mm treated softwood rails and posts fit with metal angle straps. Posts at 2.4m c/c fixed in concrete.
 - Play Area Gate
1.1 m high, 1.2 m wide gate with self-closing mechanism (as per RoSPA guidelines), powder coated black. Supplier: Heras or similar approved, Product: Tangorail TR800 play
- Movement of Hedgehogs
Free movement of hedgehogs between private gardens and public open space to be facilitated through the provision of openings between them (130mm x 130mm) at ground level. To prevent residents from blocking up the openings inadvertently, discreet signage should be provided above the openings to identify the holes as 'hedgehog highways'.
- BRIDGES**
- Vehicular Bridge (To Engineers details and specifications. For design intent refer to Design and Access statement)
 - Foot Bridge (To Engineers details and specifications. For design intent refer to Design and Access statement)
- Indicative location of control chamber to Engineer's details
 - Indicative location of below ground crates
 - Indicative location of headwall to Engineer's details

This document should not be relied on or used in circumstances other than those for which it was prepared and for which Chris Blandford Associates was commissioned. Chris Blandford Associates accepts no responsibility for this document to any other party other than the person by whom it was commissioned.

- KEY**
- Site / Application boundary
- FINISHES**
- F1. Proposed Vehicular Tarmac Housing Estate Road, To Engineer's specifications
Colour: Dark Grey
 - F2. Proposed Tarmac for Pedestrian Footpaths 125mm Raised Footpath, To Engineer's specifications, Colour: Light Grey
 - F3. Proposed Paving Type 1 - Shared surface. Permeable concrete block paving. Size: 200x100x80 mm thick, Supplier: Aggregate Industries or similar approved, Product: Infilta, Colour: Autumn
 - F4. Proposed Paving Type 2
Access Route to Houses / Private Gardens Concrete slab paving. Size: 450 x 450 x 50 mm thick, Supplier: Aggregate Industries or similar approved, Product: Andover textured paving, Colour: Light grey
 - F5. Proposed Paving Type 3 - Car parks. Permeable Concrete block paving. Size: 200 x 100 x 80 mm thick, Supplier: Aggregate Industries or similar approved, Product: Andover textured Infilta permeable paving, Colour: Light grey
 - F6. Proposed Paving Type 4 - LEAP access route. Permeable Concrete Paving Block, A:160 x 120mm, B:160 x 160mm, C:160 x 240mm, 60 mm thk, Supplier: Marshalls or similar approved, Product: Tegula Priora Harvest
 - F7. Proposed Breeding Paths - Pedestrian routes Min 12mm grade size, 50mm surface layer after compaction. 150mm MOT Type 1 sub-base with geotextile sheet below. Colour - golden amber.
 - F8. Proposed Decking Type 1
Hardwood timber decking, IPE FSC Hardwood, 21mm thick, 145mm wide, Colour: Natural, Finish: Plain with anti-slip strips
 - F9. Proposed Decking Type 2
Composite decking - Terrafina, Supplier: Kinley or similar approved, 21mm thick, 146mm wide, Colour: Grey Brown, Finish: Yacht-grooved,
 - F10. Safety Surfacing
Product: Rubber Bark Chippings. Supplier: Playbond or sim. Colour: Green/Brown
Depth to suit safety surfacing requirements
- Proposed Mown Paths
- UCR Pedestrian Crossing
- Proposed Granite Channels to Roads. Size 200 x 100 x 85mm thick, Supplier: Marshalls or similar approved, Colour: Dark grey
 - Proposed Kerb - To front of footpath 125mm upstand, Size: 145 x 255 x 915mm, Supplier: Marshalls or similar approved, Product: Conservation kerb, Colour: Charcoal
 - Proposed Edging - to back for footpath Concrete Edging, Size: 63 x 150 x 915 mm, Supplier: Marshalls or similar approved, Product: Conservation edging, Colour: Charcoal

P1	06/09/19	SM	Issued For Planning
PO	23/08/19	SM	Issued For Planning
Rev	Date	Drw	Revision or reason for Issue

Scale / North Point

CHRIS BLANDFORD ASSOCIATES
 landscape | environment | heritage
 The Print Rooms Studio 511 164/180 Union St Waterloo London SE1 0LH
 T +44 (0)20 7089 6480 E mail@cbastudios.com W www.cbastudios.com

Client
Castlefield International Limited

Project Title
TEVERSHAM ROAD FULBOURN

Drawing Series and Title
**1000 SERIES
 Hard Landscape Strategy - SHEET 2**

Scale @ A1	Drawn	Date
1:500	SM	AUG 2019
	Approved	Drawing Status
	RB	FOR PLANNING

Drawing number
TRF-CBA-1-GF-M2-L-1011

Revision
P1